

# FLY-1202

**iNetVu**<sup>®</sup>  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu<sup>®</sup> 1.2m Flyaway Antenna System is a highly portable, self-pointing, auto-acquire unit that is configurable with the iNetVu<sup>®</sup> 7710 Controller and can be assembled in less than 15 minutes by one person. The antenna features a 2-piece segmented glass fibre reinforced reflector with compact pedestal and is designed to be cost-effective while providing exceptional performance in a light weight package.



### Field Upgradable to Ka

#### Features

- One button auto-pointing controller
- 3 Axis motion (Ku-band), 2 axis (X-band)
- Airline transportable
- Supports manual control when required
- Designed to work with the iNetVu<sup>®</sup> 7710 Controller
- Captive hardware / fasteners
- 1.2m offset, prime focus, 2-piece thermoset molded reflector
- Supports General Dynamics 1.2m reflector
- No tools required for assembly / disassembly
- Less than 15 minutes assembly time, one person job
- Elevation-over-azimuth pedestal provides excellent stiffness characteristics and convenience for the user
- Eutelsat / Intelsat compliant
- Compact packaging, ruggedized shipping cases
- Minimal maintenance required
- Standard 2 year warranty

#### Application Versatility

If you operate in Ku-band, the FLY-1202 Flyaway System is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Disaster Management, Military, Oil & Gas Exploration, Mining, Construction, Mobile Offices and Emergency Services.

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

Nov, 2021

# FLY-1202

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

### Mechanical

Antenna Size & Material	1.2m Glass fibre reinforced polyester
Platform Geometry	Elevation over azimuth
Antenna optics	2-piece segmented, Offset feed prime focus
Optional	1-piece & 4-piece segmented
Offset angle	16.97°
Azimuth	±175°
Elevation	5° to 90°
Polarization	±95°
Elevation deploy speed	Variable 6° / sec
Peaking speed	0.2° / sec

### Environmental

Wind loading	
Operational	
No ballast or anchors	48 km/h (30 mph)
With ballast or anchors	72 km/h (45 mph)
Survival (with ballast)	145 km/h (90 mph)
Solar radiation	360 BTU / h / sq. ft
Temperature	
Operational	-30° to 55° C (-22° to 131° F)
Survival	-40° to 65° C (-40° to 149° F)
Rain	
Operational	10 cm/h
Survival	15 cm/h

### RF Interface

Radio mounting	Feed arm
Coaxial	RG6U F type (N type optional)

### Electrical

Electrical interface	24VDC 8 Amp (Max.)
Rx & Tx cables	2 RG 6 cables - 10 m (33 ft) each
Control cables	
Standard	10m (33 ft) ext. cable
Optional	up to 60m (200 ft) available

### Electrical (Continued)

	Ku-band (Linear)	X-band (Circular)
Transmit Power <sup>(1)</sup>	1 to 200 Watt	1 to 40 Watt
Receive Frequency (GHz)	10.70 – 12.75 <sup>(2)</sup>	7.25-7.75
Optional	10.70 - 11.70	
Transmit Frequency (GHz)	13.75 – 14.50	7.90-8.40
Optional	12.75 - 14.50	
Optional Ext. Ku Freq (GHz)		
Receive Frequency (GHz)	10.70 - 11.70 <sup>(1)</sup>	
Transmit Frequency (GHz)	12.75 - 14.50	
Midband Gain(±0.2 dB)		
(Rx)	41.80	37.40
(Tx)	43.30	38.10
Antenna Noise Temp. (K)	10° EL=45 30° EL=24	10° EL=50 30° EL=42
Sidelobe Envelope, Co-Pol (dBi)		
1.5° < Ø < 20°	29 - 25 Log Ø	DSCS Req.
20° < Ø < 26.3°	- 3.5	
26.3° < Ø < 48°	32 - 25 Log Ø	
48° < Ø < 180°	- 10 (averaged)	
Cross-Polarization on Axis	>35 dB	
Within 1 dB beamwidth	>30 dB	
Tx/Rx isolation	Rx: 40 dB Tx: 90 dB	Rx: 100 dB Tx: 100 dB
Feed	2 port Xpol	2 port Xpol
VSWR		

### Cases

Reflector case: 134.6 x 38.1 x 91.5 cm (53" x 15" x 36"); 46.6kg (103lbs)  
AZ/EL case: 53.4 x 59.7 x 40.6 cm (21" x 23.5" x 16"); 37.9kg (83.5 lbs)  
Tripod/feed case: 170.2 x 50.8 x 31.8 cm (67" x 20" x 12.5"); 38.3kg (84.5 lbs)  
4-10U Rack Mount case (Optional): 74 x 51 x 72 cm (29" x 20" x 28"); 32 kg (70 lbs)

### Shipping Weights & Dimensions\*

TBD

\* The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

### Notes:

<sup>(1)</sup> Depending on size and weight for feed arm mounting limitation

<sup>(2)</sup> LNB PLL Type required with stability better than ± 25 KHz

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)

www.c-comsat.com

Specifications are subject to change

Nov, 2021