

# MP-100-MOT

**iNetVu**<sup>®</sup>  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu<sup>®</sup> MP-100-MOT is a fully motorized, auto-acquire, 100cm carbon fiber manpack antenna. This robust and lightweight system will point to any programmed satellite with just the push of a button on the NEW iNetVu<sup>®</sup> 8020 Controller. C-COM's highly portable, multi-segment manpack can be hand-carried by one person and assembled in less than 10 minutes with no tools required.



Soft Case Solution (Standard)



8020 Controller



### Features

- 100 cm 7-piece carbon fibre reflector
- Single Backpack Case Solution
- Operates in Ku, Ka or X band
- Designed to work with the iNetVu<sup>®</sup> 8020 Controller
- Monitor and Control Via Front Panel display or Web Interface
- 2 or 3 Axis Motorization
- Supports manual control when required
- One button, auto-pointing controller acquires Ku-band satellite within 30 seconds
- Captive hardware / fasteners
- No tools required for assembly / disassembly
- Set-up time less than 10 minutes, one person job
- 1 Year Standard Warranty

### Application Versatility

The MP-100-MOT manpack system can be easily configured to provide quick access to satellite communications for any application that requires remote connectivity in a rugged environment. Ideally suited for applications that require a quick, simple set-up; in vertical markets such as emergency response, disaster management, public safety, broadcasting, media and more.

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)  
[www.c-comsat.com](http://www.c-comsat.com)

Specifications are subject to change

July 2021

# MP-100-MOT

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector	100 cm segmented carbon fibre
Number of Petals	7
Platform Geometry	Elevation over Azimuth
Antenna Optics	Centre Feed
Deployment Sensors	GPS antenna Compass $\pm 5^\circ$ Tilt sensor $\pm 0.05^\circ$
Azimuth	360° Continuous
Elevation	5° - 90°
Polarization	$\pm 90^\circ$
Elevation Deploy Speed	Variable, 11°/sec typ.
Azimuth Deploy Speed	Variable 11°/sec typ.
Peaking Speed	11°/sec (steps in $\pm 0.01^\circ$ )

### Environmental

Wind loading	
Operational	
With Ballast/Anchors	45 km/h (28.1 mph)
Survival	
With Ballast/Anchors	72 km/h (45 mph)
Temperature	
Operational	-20° to 55° C (-4° to 131° F)
Survival	-30° to 60° C (-22° to 140° F)
IP Protection	IP66
Humidity	0-100% (non-condensing)

### Case

Single Backpack Soft Case (Empty):	5.4 Kg (12.0 lbs)
Size:	84 x 51 x 41 cm (33.0" x 20.0" x 16.0")
Weight: 2-Axis (Incl. Ku Antenna(1)):	22.8 Kg (50.2 lbs)
3-Axis (Incl. Ku Antenna(1)):	24.5 Kg (54.0 lbs)
Optional: Hard Case Size:	94cm x 55.2cm x 41.6cm (37" x 21.75" x 16.37")
Weight (TBD)	

### Electrical

DC Input:	24VDC @ 3A (RMS)
Power Consumption:	
Idle:	12W
Operational (Max):	50W

### Modem Compatibility

The DVB-S2/ACM Tuner is an integrated part of all ManPacks. It allows the iNetVu® system the option to find the satellite with and without the use of a satellite modem. Compact and adaptable, this high performance tuner is programmable to any DVB-S or DVB-S2/ACM frequency and allows the user to pre-configure specific satellite options.

#### Open AMIP

Gilat - Skyedge llc - Capricorn 4	UHP - 100/200
iDirect - Evolution - iQ200	
Newtec - Dialog - MDM3310	

### Ku-Band (Linear)

Transmit Power	1 to 200 watt	
Feed	2 Port XPol	
	<b>Receive</b>	<b>Transmit</b>
Frequency (GHz)	10.70- 12.75 <sup>(2)</sup>	13.75 - 14.50
Optional Low Ku	10.70- 11.70 <sup>(2)</sup>	12.75 - 14.50
Feed Interface	WR75	WR75 <sup>(3)</sup>
Midband Gain ( $\pm .2$ dBi)	40.10	41.40
Sidelobe Envelope Co-Pol (dBi)		
100 $\lambda$ /D <sup>2</sup> < $\Theta$ < 7°	35-25 Log $\Theta$	
7° < $\Theta$ < 9.2°	13.9	
9.2° < $\Theta$ < 48°	38-25 Log $\Theta$	
48° < $\Theta$ < 180°	-4 Typical	
Cross-Polarization on Axis	>35 dB	
Within 1dB Beamwidth	>30 dB	
Tx/Rx Isolation	40 dB	85 dB
VSWR	1.3:1	1.3:1

### Ka-Band (Circular)

	<b>Receive</b>	<b>Transmit</b>
Operating Frequency (GHz)	19.20 - 21.20 <sup>(2)</sup>	29.0 - 31.0
Midband Gain ( $\pm .2$ dBi)	44.50	47.60
Polarization X-POL	LHCP/RHCP	
Feed Interface	WR-42	WR-28
VSWR	<1.5:1	<1.25:1
Isolation (dB)	>55	>55

### X-Band (Circular)

	<b>Receive</b>	<b>Transmit</b>
Operating Frequency (GHz)	7.25 - 7.75 <sup>(2)</sup>	7.90 - 8.40
Midband Gain ( $\pm .5$ dB)	36.40	37.0
Polarization X-POL	LHCP/RHCP	
Sidelobe Compliant with	DSCS Req.	
Feed Interface	WR-112	WR-112
VSWR	<1.25:1	<1.25:1
Isolation (dB)	>23	>23

### Shipping Weights & Dimensions\*

Shipping Soft Case Size:	92 x 61 x 46cm (36.0" x 24.0" x 18.0")
Shipping Weight:	2-Axis (Incl. Ku Antenna(1)): 27.7 Kg (61.0 lbs)
	3-Axis (Incl. Ku Antenna(1)): 29.5 Kg (65.0 lbs)

\* The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements

Notes:

<sup>(1)</sup> Weight indicated includes 4W BUC, LNB and 5m(16ft) Cables

<sup>(2)</sup> LNB PLL Type required with stability better than  $\pm 10$  KHz

<sup>(3)</sup> Maximum BUC dims supported: 9.8 cm x 9.8 cm x 4.2 cm (3.9" x 3.9" x 1.7"); 0.5Kg(1.1lbs)  
Larger BUCs must use quick disconnect flex waveguide

**C-COM**  
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)

www.c-comsat.com

Specifications are subject to change

July 2021